

GPS150C

Cummins diesel generator | Open set

Designed and manufactured in the United Kingdom

150 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Cummins

6BTAA5.9G6

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Cummins 6BTAA5.9G6

ALTERNATOR

Stamford UCI274E1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

140 kVA

112 kW

STANDBY POWER / ESP

150 kVA

120 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	150	120	140	112
200	PS	150	120	140	112
208	PS	150	120	140	112
220	SD	150	120	140	112
230	SD	150	120	140	112
240	SD	150	120	140	112
380	SS	150	120	140	112
400	SS	150	120	140	112
415	SS	150	120	140	112

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS150C | Cummins 6BTAA5.9G6 | Open set

ENGINE

Manufacturer	Cummins
Model	6BTAA5.9G6
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	5.9L
Bore	102mm
Stroke	120mm
Compression ratio	16.5:1
Cooling	Liquid Cooled
Coolant capacity	9.1L
Oil capacity	16.4

ALTERNATOR

Manufacturer	Stamford
Model	UCI274E1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 18 L/h	75% LOAD 27 L/h	100% LOAD 35 L/h	110% LOAD 37 L/h
----------------------------------	----------------------------------	-----------------------------------	-----------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT 1469.65 kg	FUEL TANK 310 L
--	----------------------------------

Reference frame 9069GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

SPECIFY YOUR PROJECT

Tell us your site load, required voltage and phase, prime or standby duty, ambient conditions and installation requirements. GenPro will confirm a suitable build and its exact specification.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12