

GPS150PS

Perkins diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

150 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Perkins 1106A-70TG1

ALTERNATOR

Stamford UCI274E1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative GenPro enclosure; final build may vary.

PRIME POWER / PRP

136 kVA

109 kW

STANDBY POWER / ESP

150 kVA

120 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	150	120	137	110
200	PS	150	120	136	109
208	PS	150	120	137	110
220	SD	150	120	135	108
230	SD	150	120	136	109
240	SD	150	120	137	110
380	SS	150	120	135	108
400	SS	150	120	136	109
415	SS	150	120	137	110

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS150PS | Perkins 1106A-70TG1 | Acoustic canopied

ENGINE

Manufacturer	Perkins
Model	1106A-70TG1
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Mechanical
Cylinders	6
Arrangement	In Line
Displacement	7.01L
Bore	105mm
Stroke	127mm
Compression ratio	18.2:1
Cooling	Liquid Cooled
Coolant capacity	21.0L
Oil capacity	16.5L

ALTERNATOR

Manufacturer	Stamford
Model	UCI274E1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 15.9 L/h	75% LOAD 22.7 L/h	100% LOAD 30.28 L/h	110% LOAD 33.8 L/h
------------------------------------	------------------------------------	--------------------------------------	-------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
3208 x 1164 x 1778	2247.4 kg	325 L

Reference frame 2400E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
1106A-70TG1	Leroy Somer TAL044H	400 / 3	150	135
1106A-70TG1	KWise C274G120	400 / 3	153	138

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12