

GPS200P

Perkins diesel generator | Open set

Designed and manufactured in the United Kingdom

200 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Perkins

1106A-70TAG3

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Perkins 1106A-70TAG3

ALTERNATOR

Stamford UCI274H1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

184 kVA

147 kW

STANDBY POWER / ESP

204 kVA

163 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	203	162	182	146
200	PS	204	163	184	147
208	PS	204	163	184	147
220	SD	203	162	183	146
230	SD	204	163	184	147
240	SD	204	163	184	147
380	SS	203	162	183	146
400	SS	204	163	184	147
415	SS	204	163	184	147

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS200P | Perkins 1106A-70TAG3 | Open set

ENGINE

Manufacturer	Perkins
Model	1106A-70TAG3
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Mechanical
Cylinders	6
Arrangement	In Line
Displacement	7.01L
Bore	105mm
Stroke	135mm
Compression ratio	16:1
Cooling	Liquid Cooled
Coolant capacity	21.0L
Oil capacity	18.0L

ALTERNATOR

Manufacturer	Stamford
Model	UCI274H1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 20.2 L/h	75% LOAD 32 L/h	100% LOAD 41.4 L/h	110% LOAD 45.1 L/h
-----------------------------	---------------------------	------------------------------	------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
2433 x 755 x 1565	1651.85 kg	310 L

Reference frame 9069GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
1106A-70TAG3	Leroy Somer TAL044L	400 / 3	200	180

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12