

GPS350SS

Scania diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

350 kVA

ROUNDED CATALOGUE CLASS



Representative GenPro enclosure; final build may vary.

SELECTED CONFIGURATION

ENGINE

Scania DC13320A-02-61

ALTERNATOR

Stamford S4L1D-E41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

PRIME POWER / PRP

351 kVA

281 kW

STANDBY POWER / ESP

Confirm on enquiry

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	Confirm	Confirm	350	280
200	PS	Confirm	Confirm	351	281
208	PS	Confirm	Confirm	352	282
220	PS	Confirm	Confirm	350	280
220	SD	Confirm	Confirm	350	280
230	SD	Confirm	Confirm	351	281
240	SD	Confirm	Confirm	352	282
254	SD	Confirm	Confirm	350	280
380	SS	Confirm	Confirm	350	280
400	SS	Confirm	Confirm	351	281
415	SS	Confirm	Confirm	352	282
440	SS	Confirm	Confirm	350	280

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation. Confirm = no published value; confirm on enquiry.

Technical specification

GPS350SS | Scania DC13320A-02-61 | Acoustic canopied

ENGINE

Manufacturer	Scania
Model	DC13320A-02-61
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	6
Arrangement	In Line
Displacement	12.7L
Bore	130mm
Stroke	160mm
Compression ratio	21.3:1
Cooling	Liquid Cooled
Coolant capacity	38L
Oil capacity	36L

ALTERNATOR

Manufacturer	Stamford
Model	S4L1D-E41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 36.2 L/h	75% LOAD 52.1 L/h	100% LOAD 69.2 L/h	110% LOAD Confirm on enquiry
------------------------------------	------------------------------------	-------------------------------------	---

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm) 3958 x 1504 x 2384	REFERENCE WEIGHT 3449.2 kg	FUEL TANK 500 L
--	---	----------------------------------

Reference frame 2900E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

SPECIFY YOUR PROJECT

Tell us your site load, required voltage and phase, prime or standby duty, ambient conditions and installation requirements. GenPro will confirm a suitable build and its exact specification.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12