

GPS400P

Perkins diesel generator | Open set

Designed and manufactured in the United Kingdom

400 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Perkins

2206A-E13TAG2

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Perkins 2206A-E13TAG2

ALTERNATOR

Stamford S4L1D-E41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

356 kVA

285 kW

STANDBY POWER / ESP

403 kVA

322 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	380	304	350	280
200	PS	403	322	356	285
208	PS	400	320	357	286
220	PS	380	304	350	280
220	SD	380	304	350	280
230	SD	403	322	356	285
240	SD	400	320	357	286
254	SD	380	304	350	280
380	SS	380	304	350	280
400	SS	403	322	356	285
415	SS	400	320	357	286
440	SS	380	304	350	280

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS400P | Perkins 2206A-E13TAG2 | Open set

ENGINE

Manufacturer	Perkins
Model	2206A-E13TAG2
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	12.5L
Bore	130mm
Stroke	157mm
Compression ratio	16.3:1
Cooling	Liquid Cooled
Coolant capacity	51.4L
Oil capacity	40.0L

ALTERNATOR

Manufacturer	Stamford
Model	S4L1D-E41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 37 L/h	75% LOAD 54 L/h	100% LOAD 71 L/h	110% LOAD 80 L/h
---------------------------	---------------------------	----------------------------	----------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
3182 x 1180 x 2057	3030.1 kg	730 L

Reference frame 9007GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
2206A-E13TAG2	Leroy Somer TAL046H	400 / 3	400	356

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12