

GPS400S

Scania diesel generator | Open set

Designed and manufactured in the United Kingdom

400 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Scania

DC13320A-02-62

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Scania DC13320A-02-62

ALTERNATOR

Stamford S4L1D-F41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

401 kVA

321 kW

STANDBY POWER / ESP

Confirm on enquiry

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	Confirm	Confirm	400	320
200	PS	Confirm	Confirm	401	321
208	PS	Confirm	Confirm	402	322
220	PS	Confirm	Confirm	400	320
220	SD	Confirm	Confirm	400	320
230	SD	Confirm	Confirm	401	321
240	SD	Confirm	Confirm	402	322
254	SD	Confirm	Confirm	400	320
380	SS	Confirm	Confirm	400	320
400	SS	Confirm	Confirm	401	321
415	SS	Confirm	Confirm	402	322
440	SS	Confirm	Confirm	400	320

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation. Confirm = no published value; confirm on enquiry.

Technical specification

GPS400S | Scania DC13320A-02-62 | Open set

ENGINE

Manufacturer	Scania
Model	DC13320A-02-62
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	6
Arrangement	In Line
Displacement	12.7L
Bore	130mm
Stroke	160mm
Compression ratio	21.3:1
Cooling	Liquid Cooled
Coolant capacity	38L
Oil capacity	36L

ALTERNATOR

Manufacturer	Stamford
Model	S4L1D-F41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 40.6 L/h	75% LOAD 58.7 L/h	100% LOAD 80 L/h	110% LOAD Confirm on enquiry
------------------------------------	------------------------------------	-----------------------------------	---

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

Dimensions, weight, fuel tank and model-specific drawing are confirmed with the quotation.

No complete matching frame data is published for this selected configuration.

SPECIFY YOUR PROJECT

Tell us your site load, required voltage and phase, prime or standby duty, ambient conditions and installation requirements. GenPro will confirm a suitable build and its exact specification.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12