

GPS60B

Baudouin diesel generator | Open set

Designed and manufactured in the United Kingdom

60 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Baudouin

4M06G10D0/S

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Baudouin 4M06G10D0/S

ALTERNATOR

Stamford S1L2-Y1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

52 kVA

42 kW

STANDBY POWER / ESP

57 kVA

46 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
200	PS	57	46	52	42
208	PS	57	46	52	42
230	SD	57	46	52	42
240	SD	57	46	52	42
400	SS	57	46	52	42
415	SS	57	46	52	42

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS60B | Baudouin 4M06G10D0/S | Open set

ENGINE

Manufacturer	Baudouin
Model	4M06G10D0/S
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	4
Arrangement	In Line
Displacement	2.3L
Bore	89mm
Stroke	92mm
Compression ratio	17.5:1
Cooling	Liquid Cooled
Coolant capacity	12.9L
Oil capacity	9.2L

ALTERNATOR

Manufacturer	Stamford
Model	S1L2-Y1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS540
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>100%

REFERENCE FUEL CONSUMPTION

50% LOAD 6 L/h	75% LOAD 8.9 L/h	100% LOAD 11.9 L/h	110% LOAD 13.3 L/h
---------------------------------	-----------------------------------	-------------------------------------	-------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT 712.6 kg	FUEL TANK 125 L
--	----------------------------------

Reference frame 9045GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
4M06G10D0/S	Leroy Somer TAL042G	400 / 3	55	50
4M10G2D0/S	Stamford UCI274C1	230 / 1	60	60

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12