

GPS70PS

Perkins diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

70 kVA

ROUNDED CATALOGUE CLASS



Representative GenPro enclosure; final build may vary.

SELECTED CONFIGURATION

ENGINE

Perkins 1104A-44TG1

ALTERNATOR

Stamford UCI224F1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

PRIME POWER / PRP

66 kVA

53 kW

STANDBY POWER / ESP

72 kVA

58 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	72	58	66	53
200	PS	72	58	66	53
208	PS	72	58	66	53
220	PS	61	49	55	44
220	SD	72	58	65	52
230	SD	72	58	66	53
240	SD	72	58	66	53
254	SD	61	49	55	44
380	SS	72	58	65	52
400	SS	72	58	66	53
415	SS	72	58	66	53
440	SS	61	49	55	44

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS70PS | Perkins 1104A-44TG1 | Acoustic canopied

ENGINE

Manufacturer	Perkins
Model	1104A-44TG1
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Mechanical
Cylinders	4
Arrangement	In Line
Displacement	4.4L
Bore	105mm
Stroke	127mm
Compression ratio	17.25:1
Cooling	Liquid Cooled
Coolant capacity	13.0L
Oil capacity	8.0L

ALTERNATOR

Manufacturer	Stamford
Model	UCI224F1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 8 L/h	75% LOAD 11.2 L/h	100% LOAD 14.8 L/h	110% LOAD 16.5 L/h
--------------------------	-----------------------------	------------------------------	------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
2286 x 1104 x 1620	1362.25 kg	210 L

Reference frame 2105E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
1104A-44TG1	Stamford UCI224G1	400 / 3	72	66
1103A-33TG2	Stamford S1L2-Y1	400 / 3	66	61
1104A-44TG1	Leroy Somer TAL044A	400 / 3	72	66
1103A-33TG2	Leroy Somer TAL044A	400 / 3	67	61

Engineering data above apply only to the selected configuration on page 1. 2 further class configurations are listed on the product page.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12