

GPS710S

Scania diesel generator | Open set

Designed and manufactured in the United Kingdom

710 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Scania

DC16093A-02-54

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Scania DC16093A-02-54

ALTERNATOR

Stamford HCI544F1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

647 kVA

518 kW

STANDBY POWER / ESP

711 kVA

569 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	709	567	644	515
200	PS	711	569	647	518
208	PS	712	570	648	518
220	PS	714	571	649	519
220	SD	709	567	646	517
230	SD	711	569	647	518
240	SD	712	570	648	518
254	SD	714	571	649	519
380	SS	709	567	646	517
400	SS	711	569	647	518
415	SS	712	570	648	518
440	SS	714	571	649	519

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS710S | Scania DC16093A-02-54 | Open set

ENGINE

Manufacturer	Scania
Model	DC16093A-02-54
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	8
Arrangement	At Vee
Displacement	16.4L
Bore	130mm
Stroke	154mm
Compression ratio	16.7:1
Cooling	Liquid Cooled
Coolant capacity	68L
Oil capacity	48L

ALTERNATOR

Manufacturer	Stamford
Model	HCI544F1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 63.3 L/h	75% LOAD 93.1 L/h	100% LOAD 129.3 L/h	110% LOAD 143 L/h
-----------------------------	-----------------------------	-------------------------------	-----------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT 3273.8 kg

Reference frame Error (9077GA) (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
DC16093A-02-54	Stamford S5L1D-F41	400 / 3	711	647
DC16093A-02-54	Leroy Somer TAL0473F	400 / 3	713	648

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12