

GPS730BS

Baudouin diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

730 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Baudouin 6M33G715/5

ALTERNATOR

Stamford S5L1D-F41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative GenPro enclosure; final build may vary.

PRIME POWER / PRP

658 kVA

526 kW

STANDBY POWER / ESP

725 kVA

580 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The GPS model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
380	SS	722	578	657	526
400	SS	725	580	658	526
415	SS	726	581	659	527

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

GPS730BS | Baudouin 6M33G715/5 | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	6M33G715/5
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	19.6L
Bore	150mm
Stroke	185mm
Compression ratio	15:1
Cooling	Liquid Cooled
Coolant capacity	79.6L
Oil capacity	64L

ALTERNATOR

Manufacturer	Stamford
Model	S5L1D-F41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1.0% Regulation%
Insulation class	H
Excitation	Brushless
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 67.1 L/h	75% LOAD 100 L/h	100% LOAD 136.3 L/h	110% LOAD 153.3 L/h
-----------------------------	----------------------------	-------------------------------	-------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm) 4908 x 2164 x 2658	REFERENCE WEIGHT 6940.75 kg	FUEL TANK 1120 L
---	---------------------------------------	----------------------------

Reference frame 5100E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
6M33G715/5	Stamford HCI544F1	400 / 3	724	658
6M33G2D0/S	Stamford S5L1D-F41	400 / 3	724	658
6M33G715/5	Leroy Somer TAL0473F	400 / 3	726	659

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

GenPro technical specification | Reviewed 2026-10-12