# PPG1550BS

**1550 kVA**
ROUNDED CATALOGUE CLASS

Baudouin diesel generator | Acoustic canopied

**Designed and manufactured in the United Kingdom**

ENGINE PLATFORM

## Baudouin

**12M33G1500/5**

Model-specific drawing supplied with quotation.

### SELECTED CONFIGURATION

ENGINE
**Baudouin 12M33G1500/5**

ALTERNATOR
**Stamford S7L1D-C41**

ELECTRICAL OUTPUT
**400 V | 3-phase | 50 Hz**

Configuration and appearance are confirmed with the quotation.

**PRIME POWER / PRP**
**1389 kVA** 1111 kW

**STANDBY POWER / ESP**
**1529 kVA** 1223 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

## PUBLISHED ELECTRICAL RATINGS

| Voltage (V) | Connection | ESP (kVA) | ESP (kW) | PRP (kVA) | PRP (kW) |
|---|---|---|---|---|---|
| 380 | SS | 1528 | 1222 | 1388 | 1110 |
| 400 | SS | 1529 | 1223 | 1389 | 1111 |

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.


Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.

# Technical specification

**PPG1550BS** | Baudouin **12M33G1500/5** | Acoustic canopied

## ENGINE

| | |
|---|---|
| Manufacturer | Baudouin |
| Model | **12M33G1500/5** |
| Aspiration | Turbocharged |
| Combustion | Direct Injection |
| Cycle | 4 Stroke |
| Governor | Electronic |
| Cylinders | 12 |
| Arrangement | At Vee |
| Displacement | 39.2L |
| Bore | 150mm |
| Stroke | 185mm |
| Compression ratio | 15:1 |
| Cooling | Liquid Cooled |
| Coolant capacity | 188L |
| Oil capacity | 160L |

## ALTERNATOR

| | |
|---|---|
| Manufacturer | Stamford |
| Model | **S7L1D-C41** |
| Type | Brushless |
| Phases | 3 |
| Bearings | 1 |
| Poles | 4 |
| Leads | 6 |
| AVR | **MX341** |
| Voltage regulation | 1% |
| Insulation class | H |
| Excitation | PMG |
| Winding | 312 |
| Harmonic content | <5.00% |
| Short circuit | >300% |

## REFERENCE FUEL CONSUMPTION

| 50% LOAD | 75% LOAD | 100% LOAD | 110% LOAD |
|---|---|---|---|
| **146.2 L/h** | **214.4 L/h** | **296.9 L/h** | **330.5 L/h** |

Reference figures vary with operating conditions and the confirmed duty.

## INSTALLATION INFORMATION

Dimensions, weight, fuel tank and model-specific drawing are confirmed with the quotation.

No complete matching frame data is published for this selected configuration.

## SPECIFY YOUR PROJECT

Tell us your site load, required voltage and phase, prime or standby duty, ambient conditions and installation requirements. PPG will confirm a suitable build and its exact specification.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
PPG technical specification | Reviewed 2026-10-12


Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.