PPG360S

360 kVA
ROUNDED CATALOGUE CLASS

Scania diesel generator | Open set

Designed and manufactured in the United Kingdom

ENGINE PLATFORM

Scania

DC09072A-02-14

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Scania DC09072A-02-14

ALTERNATOR

Stamford S4L1D-E41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

330 kVA 264 kW

STANDBY POWER / ESP

360 kVA 288 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	360	288	329	263
200	PS	360	288	330	264
208	PS	362	290	331	265
220	PS	363	290	332	266
220	SD	360	288	330	264
230	SD	360	288	330	264
240	SD	362	290	331	265
254	SD	363	290	332	266
380	SS	360	288	330	264
400	SS	360	288	330	264
415	SS	362	290	331	265
440	SS	363	290	332	266

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

PPG360S | Scania **DC09072A-02-14** | Open set

ENGINE

Manufacturer	Scania
Model	**DC09072A-02-14**
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	5
Arrangement	In Line
Displacement	9.3L
Bore	130mm
Stroke	140mm
Compression ratio	16:1
Cooling	Liquid Cooled
Coolant capacity	37L
Oil capacity	36L

ALTERNATOR

Manufacturer	Stamford
Model	**S4L1D-E41**
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	**AS440**
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
32.5 L/h	**48.2 L/h**	**67 L/h**	**73.5 L/h**

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT	FUEL TANK
2443.15 kg	**730 L**

Reference frame 9007GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
DC13071A-02-01	Stamford **S4L1D-E41**	400 / 3	Confirm	360

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
PPG technical specification | Reviewed 2026-10-12

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.