PPG40BS

40 kVA

ROUNDED CATALOGUE CLASS

Baudouin diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom



Representative PPG enclosure; final build may vary.

SELECTED CONFIGURATION

ENGINE

Baudouin 4M06G8D0/S

ALTERNATOR

Stamford S1L2-N1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

PRIME POWER / PRP

39.9 kVA 31.9 kW

STANDBY POWER / ESP

44 kVA 35.2 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
200	PS	44	35.2	39.9	31.9
208	PS	44.1	35.3	40	32
230	SD	44	35.2	39.9	31.9
240	SD	44.1	35.3	40	32
400	SS	44	35.2	39.9	31.9
415	SS	44.1	35.3	40	32

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

PPG40BS | Baudouin **4M06G8D0/S** | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	**4M06G8D0/S**
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	4
Arrangement	In Line
Displacement	2.3L
Bore	89mm
Stroke	92mm
Compression ratio	17.5:1
Cooling	Liquid Cooled
Coolant capacity	16L
Oil capacity	11.5L

ALTERNATOR

Manufacturer	Stamford
Model	**S1L2-N1**
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	**AS540**
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>100%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
4.7 L/h	**7 L/h**	**9.5 L/h**	**10.8 L/h**

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
2240 x 1038 x 1378	**1008.7 kg**	**80 L**

Reference frame 1900E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
4M06G6D0/S	Stamford **S1L2-J1**	400 / 3	34.6	31.7
4M06G6D0/S	Leroy Somer **TAL042C**	400 / 3	34.8	31.8
4M06G6D0/S	KWise **C184G28**	400 / 3	34.6	31.4

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
PPG technical specification | Reviewed 2026-10-12

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.