PPG50B

50 kVA

ROUNDED CATALOGUE CLASS

Baudouin diesel generator | Open set

Designed and manufactured in the United Kingdom

ENGINE PLATFORM

Baudouin

4M06G50/5

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Baudouin 4M06G50/5

ALTERNATOR

Stamford S1L2-N1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

45 kVA 36 kW

STANDBY POWER / ESP

50 kVA 40 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
200	PS	50	40	45	36
208	PS	50	40	45	36
230	SD	50	40	45	36
240	SD	50	40	45	36
400	SS	50	40	45	36
415	SS	50	40	45	36

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

PPG50B | Baudouin **4M06G50/5** | Open set

ENGINE

Manufacturer	Baudouin
Model	**4M06G50/5**
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	4
Arrangement	In Line
Displacement	2.3L
Bore	89mm
Stroke	92mm
Compression ratio	17.5:1
Cooling	Liquid Cooled
Coolant capacity	8.4L
Oil capacity	11.5L

ALTERNATOR

Manufacturer	Stamford
Model	**S1L2-N1**
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	**AS540**
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>100%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
5.4 L/h	**8 L/h**	**10.7 L/h**	**11.7 L/h**

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT	FUEL TANK
667.7 kg	**125 L**

Reference frame 9045GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
4M06G50/5	Leroy Somer **TAL042F**	400 / 3	50	45
4M06G50/5	KWise **C224G40**	400 / 3	51	47
4M06G50/5	Stamford **UCI224G1**	230 / 1	47	43.1

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
PPG technical specification | Reviewed 2026-10-12

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.