PPG570S

570 kVA
ROUNDED CATALOGUE CLASS

Scania diesel generator | Open set

Designed and manufactured in the United Kingdom

ENGINE PLATFORM

Scania

DC16093A-02-51

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Scania DC16093A-02-51

ALTERNATOR

Stamford HCI544E1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

520 kVA 416 kW

STANDBY POWER / ESP

571 kVA 457 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	569	455	519	415
200	PS	571	457	520	416
208	PS	572	458	520	416
220	PS	573	458	521	417
220	SD	569	455	518	414
230	SD	571	457	520	416
240	SD	572	458	520	416
254	SD	573	458	521	417
380	SS	569	455	518	414
400	SS	571	457	520	416
415	SS	572	458	520	416
440	SS	573	458	521	417

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.

Technical specification

PPG570S | Scania **DC16093A-02-51** | Open set

ENGINE

Manufacturer	Scania
Model	**DC16093A-02-51**
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	8
Arrangement	At Vee
Displacement	16.4L
Bore	130mm
Stroke	154mm
Compression ratio	16.7:1
Cooling	Liquid Cooled
Coolant capacity	68L
Oil capacity	48L

ALTERNATOR

Manufacturer	Stamford
Model	**HCI544E1**
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	**AS440**
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD	75% LOAD	100% LOAD	110% LOAD
52.3 L/h	**75.6 L/h**	**100.3 L/h**	**111.5 L/h**

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

REFERENCE WEIGHT	FUEL TANK
3496.8 kg	**590 L**

Reference frame 9090GA (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
DC16093A-02-51	Stamford **S5L1D-D41**	400 / 3	568	516

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.
PPG technical specification | Reviewed 2026-10-12

Perkins Power Generators is a trading name of GenPro Power Solutions.
Exact build, performance and delivery scope are confirmed in the quotation.